

Water Quality Demo Outfits

WaterLink® Spin Touch® DW Sales Demonstration Outfit

Featuring the WaterLink® Spin Touch® DW

Order Code 4-3085



Code 4-3085

Sales Demonstration Outfit

- WaterLink® Spin Touch® DW photometer
- Duo-Soft Model Water Softener
- Pump and Connection Tubing
- Soap Consumption Demonstration
- Lockable, Foam-Lined Carrying Case



Optional Add-On Kits

- Precipitation Demonstration (0.2-3.0 ppm) · 50 Tests
Order Code **8124**
- TRACER PocketTester TDS/Salinity/Conductivity/Temp
Order Code **1749** [see page 6]

Test disks are not included. See page 3 for disks.



Code 8124

Water Quality Demo Outfits

LaMotte Model AT-Q and AT Visual series outfits are the most popular and effective sales tools for on-site demonstrations. The tests clearly demonstrate the benefits between untreated and treated water.

AT-Q Digital Series**

Featuring the ColorQ DW digital colorimeter

- New digital versions
- New rugged case with locks
- Fast & simple tests
- More custom options
- Competitive pricing

Includes
Diagrammed
Quick-Start
Guide!



Customize Your Water Quality
Sales Demonstrations.

Choose the Softener that
Meets Your Needs!



AT-Q with Model S
Code 4-3051-01



AT-Q with DuoSoft
Code 4-3055-01



AT-Q with DirectFlo
Code 4-3071-01



AT-Q with DirectFlo
DuoSoft
Code 4-3075-01

AT-Q Digital Kit Tests [9 Included]

	Hardness	pH	Iron	Nitrate	Chlorine Free & Total	Sulfide	Precipitation	Soap Consumption
Range	1-41 gpg*	5-9	0-3.0 ppm*	0-25	0-10 ppm	0-3.0 ppm*	Before/After	Before/After
Resolution	1 gpg	0.5 pH	0.5	1 ppm	0.2 ppm	0.2 ppm	—	—
Number of Tests	140	70	50	50	50	120	100	100

*Higher Concentrations by dilution; instructions included. **⚠️ WARNING: Cancer - www.P65Warnings.ca.gov

AT Visual Series**

Includes
Diagrammed
Quick-Start
Guide!



AT with Model S
Code 4-3003-02



AT with DuoSoft
Code 4-3015-01



AT with DirectFlo
Code 4-3010-01



AT with DirectFlo
DuoSoft
Code 4-3018-01

AT Visual Kit Tests [5 Included]

	Hardness	pH	Iron	Precipitation	Soap Consumption
Range	1 drop = 10 ppm/ 20 ppm/10 gpg	5.0-10 ppm	0.5-10 ppm*	Before/After	Before/After
Number of Tests	100	100	100	100	100

*Higher Concentrations by dilution; instructions included. **⚠️ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Optional Add-On Kits and TDS Meter:

- Chlorine [0.2-3.0 ppm] · 50 Tests
Code 4-3006-01
- Nitrate [0-15 ppm] · 50 Tests
Code 4-3004-01
- Salinity, TDS, Con Tracer Meter
Code 1749 [see page 4]

Water Quality Demo Outfits

Demonstration Water Softeners

Generate high-quality softened water in seconds. Clear acrylic column is durable and visually impressive. Flexible intake and outlet hoses have plastic clamps that prevent spillage. Rubber adapter on intake hose attaches to faucet. Available in four different models to suit your demonstration needs.



Now with
Quick Connect
Couplings!

Refills Available!



DuoSoft

Order Code: 1022-FLD
Carbon and Resin Refill Code: R-1022

The LaMotte twin-chambered softener clearly demonstrates the advantages of advanced two-part treatment systems. Customize one today to demonstrate the true effectiveness of your treatment system.

- Treat tapwater in one pass with a two-chambered softener
- A filled Duo-Soft is furnished in the Model AT-40 and AT-Q-40 outfit
- Also available: Order Code 1022 DuoSoft unit empty to fill with your choice of media.



DirectFlo DuoSoft

Order Code: 1028
Carbon and Resin Refill Code: R-1022

- Unique gravity fed design works with any size faucet, eliminating messy hoses!
- Effectively combines two water treatments in one pass
- Twin 4" chambers (10.25" total height) with carbon in the top chamber and resin in the bottom chamber
- Designed to ensure only water coming out the side outlet has received both treatments.



Model S

Order Code: 1002
Resin Refill Code: R-1002

An 8" resin column (10.25" total height) that softens up to 70 gallons of medium hard water (7 gpg hardness) before requiring regeneration or fresh resin. Model S softener is furnished in the Model AT-38 and AT-Q-38 outfits.



DirectFlo Softener

Order Code: 1026
Resin Refill Code: R-1002

- Unique gravity fed design works with any size faucet, eliminating messy hoses!
- 8" resin column (10.25" total height) softens up to 70 gallons of hard water (7 gpg) before regeneration
- Designed to ensure only treated water comes out of the side outlet.



Recommended Pumps and Tubing

Order Code: 9430

Large Submersible Pump for DuoSoft Softener 1022.

Order Code: 9480

1/2" Tubing w/Quick Connect fitting for Large Pump [code 23384].

Order Code: 9440

Small Submersible Pump for Model S Softener 1002.

Order Code: 3-1025-tubing

1/4" Tubing w/Quick Connect fitting for Small Pump [code 23379]



Quick Connect Connectors

Order Code: 3-1023M

Quick Connect Male Fitting.

Order Code: 3-1023F

Quick Connect Female Fitting.

TRACER PockeTester TDS/Salinity/Conductivity/Temp

Code 1749

- Easy to use with push-button calibration
- TDS 0-9,900 ppm; Salinity 0-9,900 ppm; Con 0-19.99 mS; Temp 32-149 F
- Automatic temperature compensation
- Memory can store up to 25 readings

